



NOTES:
 DOTTED LINES DENOTE WIRES OFF THE PCB.
 P1 = PAGE 1.
 E4 = GRID REF. E4.
 ADJUST BIAS TO -50 VOLTS APPROX
 (NO SIGNAL CONDITION)

UNSPECIFIED HOLE DATA			
	A		H
	B		J
	C		K
12	0998	16/8/95	D
11	0868	12/4/95	E
10	0688	17-11-94	F
ISS	ECO NUMBER	DATE	G

MATERIAL		DIMENSIONS IN	
MATERIAL THICKNESS		TOLERANCE (UNLESS OTHERWISE STATED)	
INTERNAL BEND RADIUS		DIMENSIONAL	
EXTERNAL B/A		CENTRES	
BEND D/E		ANGULAR	
DRAWN CJR	DATE 29/6/93	MODEL	2500SL-X
CHECKED <i>RSMT</i>	DATE 1/8-95		5881 VALVE TYPE
APPROVED	DATE		

Marshall

COPYRIGHT EXISTS ON THIS DOCUMENT. IT MUST NOT BE USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SUPPLIED AND MUST NOT BE REPRODUCED OR IN PART) WITHOUT WRITTEN PERMISSION FROM

© MARSHALL AMPLIFICATION PLC
 GERRARD ROAD, SLETONLEY, MILTON KEYNES, MK1 1DG.
 TEL 120862754-11 FAX 120861376118

TITLE		DWG.No		ISSUE	
POWER AMP CCT		2500-60-58		12	